



Impellerparameter JETFAN-90-V2 (© 2012 by Gernot Neuböck)

Motor		Battery		Parameter of fan				Choice of motor				Notes	
Type of motor	Brand	Used battery	Cells (LIPO)	I [A]	U [V]	V/Cell	Thrust [Kg]	ETA complete system [%]	Version of fan	Go	No Go	Preferred motor	Temperature range of used motor
HK 3226-900KV	Scorpion	Wellp. 5000 SE 40C	12	53,28	46,17	3,85	3,50	54	V2	X		XXX	SUPER COOL RUNNING
HET 700-83-975KV	HET	XCell 5500 35C	12	71,00	44,80	3,73	4,45	59	V2	X		XXX	SUPER COOL RUNNING
HET 700-83-1080KV	HET	XCell 5500 35C	12	82,00	41,00	3,42	4,60	59	V2	X		XXX	SUPER COOL RUNNING
LBP 4082-B-1000KV	Leopard	Lipolice 55C 5000	12	85,62	45,26	3,77	4,85	56	V2	X		XXX	SUPER COOL RUNNING
HET 700-68-1200KV	HET	XCell 4200 35C	12	93,97	44,94	3,75	5,10	55	V2	X		XXX	SUPER COOL RUNNING
LBP 4082-B-1250KV	Leopard	Wellp. 5000 SE 40C	12	127,30	44,10	3,68	6,20	56	V2	X		XX	NORMAL TEMPERATURE, OK